



RELAXED SERVING.

Enjoy preparing delicious meals and to serve them at the right time! With the light version you receive the advantages of the established Rieber banquet trolley at a clearly lower price. The banquet trolley light is a high class trolley made of stainless steel, with double-walled corpus and double-walled doors,

insulated. Cupboard compartment with seamlessly deep-drawn support rails for stainless steel grilles or GN containers with rail clearance of 115 mm, with tilt protection. Doors with silicone seal. Click door lock into place.

SPECIFICATIONS

Banquet trolley light, heated, (available in GN 1 x 2/1 and 2 x 2/1, with analogue controller, without gallery, etc.) made of stainless steel. Body, doors double-walled, insulated. Cupboard compartment with seamless deep-drawn support rails for stainless steel grilles or GN containers with rail clearance of 115 mm, with tilt protection. Doors with silicone seal. Click door lock into place. Child lock (can be pushed open from inside). With one push handle on face side. 4 corner bumpers. Rust-free casters in ac-

cordance with DIN 18867, part 8. Wheel diameter 200 mm. 2 fixed casters, 2 swivel casters with brakes. Circulating air heating, thermostat controller from +30 °C to +90 °C. Compartment allocation Gastronorm-compliant, for plates up to dia. 310 mm, enlarged storage space through middle console up to version 2 x 2/1 GN. ON/OFF switch, switch elements impact-protected, spiral cable, cable mounting. Rated voltage 1N AC 230 V 50 Hz/60 Hz.

SPECIFICATIONS

Typ	BKW light 1 x 2/1 GN heated		BKW light 2 x 2/1 GN heated	
External dimensions mm	777 x 837 x 1674		1490 x 837 x 1674	
Empty weight kg	120	120	200	200
Number of pushing handle(s)	1	1	1	1
Distance between support rails mm	115	70	115	70
Max. number of stainless steel grilles GN 2/1	11	18	2 x 11	2 x 18
Storage capacity				
Dispensed plates dia. 260 mm	64	64	160	160
Plates not stacked				
Ø 260 mm	44	72	110	180
Ø 310 mm	22	36	88	144
Total connected load in kW	2,0	2,0	2,7	2,7
Order no.	88 23 01 11	88 23 01 12	88 23 02 11	88 23 02 12